

## product specifications

<b>style name</b>	intricate 20 mil
<b>style number</b>	0692V
<b>construction</b>	luxury vinyl tile
<b>class / ASTM F1700</b>	class III printed film vinyl tile, type b (embossed)
<b>nominal dimensions</b>	12 in wide, 24 in long

	<b>US units</b>	<b>metric units</b>
<b>wear layer thickness</b>	0.020 in	20 mil (0.5 mm)
<b>overall thickness</b>	0.098 in	2.5 mm
<b>actual width</b>	11.8 in	30 cm
<b>actual length</b>	23.6 in	60 cm
<b>backing class</b>	commercial grade	
<b>finish</b>	ExoGuard™	
<b>installation</b>	direct glue	
<b>recommended adhesive</b>	Shaw 4100 or S150	

## packaging

<b>square feet per carton</b>	42.63
<b>pieces per carton</b>	22
<b>weight per carton</b>	41.9 lbs

## testing

<b>slip resistance</b>	(ASTM D2047) passes
<b>static load</b>	(ASTM F970) 2000 psi
<b>residual indentation</b>	(ASTM F1914) passes
<b>flexibility</b>	(ASTM F137) passes
<b>resistance to heat</b>	(ASTM F1514) passes
<b>resistance to light</b>	(ASTM F1515) passes
<b>resistance to chemicals</b>	(ASTM F925) passes
<b>radiant panel</b>	(ASTM E648) Class 1
<b>nbs smoke</b>	(ASTM E662) <450


## warranty

10 year commercial wear  
10 year under bed when installed with Shaw 4100 or S150  
Please visit [www.shawhardsurface.com](http://www.shawhardsurface.com) for the most current warranty information.

## installation methods



monolithic



brick




basketweave




half basketweave




boxed in



herringbone



ashlar



stagger

## environmental

**indoor air quality** FloorScore® certified



Specifications are subject to nominal manufacturing variance.  
Material supply and/or manufacturing processes may necessitate changes without notice