

GROUNDWORKS™

GroundWorks is a Noise Reduction Underlayment that was engineered to reduce sound transmission within multi-level structures. It is ideal for use with luxury vinyl plank.

FEATURES

- Excellent sound suppression
- No risk of plasticizer migration with recommended Shaw adhesives
- Decreases step sound in rooms and large spaces
- Suitable over concrete, wood and hydronic radiant heated floors
- Recommended for floating or double-glue installation
- GREENGUARD GOLD Indoor Air Quality Certified®

SUGGESTED APPLICATIONS

- Hotels
- Assisted Living Units
- Multi-Family Apartments
- Military Housing
- Areas where you are concerned about IIC ratings

SPECIAL NOTE

This product is not approved for wide open areas, or areas where there are rolling loads.



APPROVED ADHESIVES

All Shaw resilient adhesives

SPECIFICATIONS

construction: Rolled polyurethane foam
 application: LVT/P and floating floors
 installation: Single glue (floating) or double glue
 warranty: Commercial Limited Warranty

	US Units	Metric
roll size:	3 ft x 33 ft 4 in 6 ft x 75 ft	0.91 x 10.15 m 1.83 x 22.9 m
thickness:	0.055 in	1.4 mm
roll weight:	14 / 63 lbs	6.35 / 28.58 kg

PERFORMANCE + TESTING

impact insulation class rating: IIC (ASTM E492-09/E989-06) When paired with the appropriate resilient flooring, results typically range from 50 –70, depending on subfloor assembly and resilient product. For specific results, please contact your account manager.

sound transmission class rating: STC (ASTM E90/E413) Is a measure of airborne sound transmission loss in an adjacent room. Floor-covering affects sound generated in the room above and below. Floor-covering does not affect STC, but floor assembly construction and amount of insulation in a ceiling.

LEED v4: EQ Credit: Low Emitting Materials GREENGUARD Gold