

## Whisper

product type:	<b>wallcovering</b>
collection:	<b>wallcovering</b>
style number:	<b>60751</b>
construction:	<b>needlebond</b>
pattern:	<b>single rib</b>
fiber:	<b>50% olefin / 50% PET polyester</b>
dye method:	<b>100% solution dyed</b>
secondary backing:	<b>SBR latex</b>
total weight:	<b>30 oz/ly</b>
roll size:	<b>72 ft X 54 in</b>
packaging:	<b>"crush proof" box</b>
warranty:	<b>one year limited warranty</b>

### recommended installation methods

#### direct glue

### performance + testing

flammability:	<b>Passes Corner Burn</b> <b>NFPA-265: UBC 8-2</b> <b>Tunnel test, Class A Rating</b> <b>ASTM E-84</b>						
acoustical:	<b>ASTM C-423-84A</b> <b>Gypsum Board NRC .20</b> <b>Acoustic Board NRC .80</b>						
tensile strength:	<b>ASTM D-5034, (LBS)</b> <table><tr><td><b>Break</b></td><td><b>Elongation</b></td></tr><tr><td><b>142 L X 132 W</b></td><td><b>195 L X 145 W</b></td></tr></table>	<b>Break</b>	<b>Elongation</b>	<b>142 L X 132 W</b>	<b>195 L X 145 W</b>		
<b>Break</b>	<b>Elongation</b>						
<b>142 L X 132 W</b>	<b>195 L X 145 W</b>						
tear (trap) strength:	<b>ASTM D-2261, (LBS)</b> <b>30 L X 25 W</b>						
abrasion resistance:	<b>ASTM D-3884</b> <table><tr><td><b>Ribs</b></td><td><b>Rapture</b></td></tr><tr><td><b># Cycle</b></td><td><b># Cycles</b></td></tr><tr><td><b>1,720</b></td><td><b>2,260</b></td></tr></table>	<b>Ribs</b>	<b>Rapture</b>	<b># Cycle</b>	<b># Cycles</b>	<b>1,720</b>	<b>2,260</b>
<b>Ribs</b>	<b>Rapture</b>						
<b># Cycle</b>	<b># Cycles</b>						
<b>1,720</b>	<b>2,260</b>						
colorfast:	<b>AATCC-165</b> <table><tr><td><b>Wet Crocking</b></td><td><b>Dry Crocking</b></td></tr><tr><td><b>5</b></td><td><b>5</b></td></tr></table>	<b>Wet Crocking</b>	<b>Dry Crocking</b>	<b>5</b>	<b>5</b>		
<b>Wet Crocking</b>	<b>Dry Crocking</b>						
<b>5</b>	<b>5</b>						
fmvss 302:	<b>Passes</b>						
electrostatic:	<b>AATCC-134</b> <b>0.2kv</b>						

